



SNARLER AT6 ABS

44hp DYNAMIC

DOHC Single Cylinder, 4-Stroke CVTech transmission. 4.2s 0-60km/h Acceleration 39° Climbing Angle

ARS

Reducing the chance of wheel lock-up during hard-braking events or when braking on rough, uneven, slipper or loose surfaces.

SMART MOVING APP

Remote access to the real-time data of vehicle through smart moving APP. Airlock / EPS Settings / Wireless Team Up / Security Guarantee / Real-Time Data

220 LB BACK LOAD

LCD DISPLAY

Monitor the key indicators of vehicle at any time through the display.

14" ALUM BIM

Front 26×08-14 Rear 26×10-14

SPECIFICATIONS

SNARLER AT6 L EPS ABS **STANDARD**

SNARLER AT6 L EPS ABS **PREMIUM**

Automatic CVT Cvtech

Automatic CVT Cytech

Front

44Hp

Front & Rear

EPS

YES

YES

44Hp

235x128x143cm

235x128x143cm

WHEELBASE

145cm 27cm

145cm

FUEL CAPACITY

23 Liter

27cm 23 Liter

Min 2 x own weight, max hitch ball: 1000 kg

Min 2 x own weight, max hitch ball: 1000 kg

2500Lbs/1135Kg

2500Lbs/1135Kg

PAYLOAD CAPACITY

270 kg

270 kg Dual-A-Arm.18cm Wheel Travel

Dual-A-Arm.18cm Wheel Travel Dual-A-Arm,21cm Wheel Travel

FRONT SUSPENSION

Oil Shock

Gas Shock

14" Aluminium

14" Aluminium Beadlock

F:26x08-14 / R:26x10-14

Dual-A-Arm,21cm Wheel Travel

F:26x08-14 / R:26x10-14

RACK

4-Wheel Hydraulic Disc Front & Rear Plastic Rack 4-Wheel Hydraulic Disc Front & Rear Plastic Rack

LED YES

Included

LED YES

Included

HANDLEBAR GUARD

Included Included

COLORS

Tensive Red / Dream Green / Smart Blue / Prairie Camo / Orange

^{*} Towing capacity is determined by the winch or trailer ball, depending on the application.









^{*} Vehicle intended for agricultural or forestry use

^{*} Towing must always be done in low gear, walking speed, on flat surface, with 4x4 system engaged, under supervision, and at your own risk.

^{*} Towing in high gear is possible but not recommended.